

Item Number EB14200604

https://www.eibabo.cn/eht-aeg/flow-heater-24kw-instantaneous-water-heater-24kw-aeg-ddle-easy-24-eb14200604



Flow heater 24KW - Instantaneous water heater 24kW AEG DDLE EASY 24

×

EHT AEG

AEG DDLE EASY 24 228842 4041056025094 EAN/GTIN

2230,24 CNY excl. VAT**

plus shipping



4-5 days* (CHN)

Instantaneous water heater 24KW AEG DDLE EASY 24 energy efficiency class A, energy efficiency classes spectrum A to G, material of the pressure vessel plastic, nominal capacity 0.4l, max. permissible operating pressure 10bar, nominal power 24kW, nominal voltage 1 380V, nominal voltage 2 400V, manual operation, analogue temperature display, type of installation Oversink/undersink, electronic power control, connected load 24 ... 24kW, bare wire heating system, safety shut-off pressure shut-off, protection class (IP) IP25, connection for cold drinking water external thread, nominal inside diameter of cold drinking water 1/2 inch (15), pipe outside diameter of cold drinking water 21.5 mm, connection Hot water external thread, nominal inside diameter of hot water connection 1/2 inch (15), pipe outside diameter of hot drinking water 21.5 mm, suitable for plastic pipe, type of control electronic, height 3.6mm, width 226mm, depth 93mm, weight 3.6kg, flow heater, electronically controlled, for supplying washbasin, kitchen sink, shower, bathtub. Electronics with good temperature comfort. Two fixed temperatures 42 °C and 55 °C with application icons. Fast control electronics for high temperature constancy Heating block made of glass fiber reinforced polyamide. 4 heating coils lying directly in the water. Measuring turbine for precise flow rate measurement, electronic air bubble detection. Largely constant outlet temperatures with pressure and inlet temperature fluctuations. Connection options for long-distance and direct tapping. For connection to XLPE plastic pipes with DVGW test mark. Easy assembly with separate mounting plate and screw cap, with assembly template, hood disassembly from the front, without screws, electrical connection from above or below. Power supply with permanent connection. Oversink installation, undersink installation possible with accessory UT 104. Connection to all commercially available closed fittings. VDE/GS mark, radio protection mark/EMC.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

