



**Fieldbus coupler ethernet TCP/IP - Fieldbus basic device  
DC24V 750-342**



**WAGO**  
750-342  
4045454527006 EAN/GTIN

**3302,97 CNY** excl. VAT\*\*  
plus shipping



15-16 days\* (CHN)

With integrated power supply=no, Input voltage at DC=24 V, Type of voltage (input voltage)=DC, Max. input current DC=0,5 A, Number of HW-interfaces industrial Ethernet=1, With optical interface=no, Supporting protocol for TCP/IP=no, Supporting protocol for PROFIBUS=no, Supporting protocol for CAN=no, Supporting protocol for INTERBUS=no, Supporting protocol for ASI=no, Supporting protocol for KNX=no, Supporting protocol for MODBUS=yes, Supporting protocol for Data-Highway=no, Supporting protocol for DeviceNet=no, Supporting protocol for SUCONET=no, Supporting protocol for LON=no, Supporting protocol for SERCOS=no, Supporting protocol for PROFINET IO=no, Supporting protocol for PROFINET CBA=no, Supporting protocol for Foundation Fieldbus=no, Supporting protocol for EtherNet/IP=yes, Supporting protocol for AS-Interface Safety at Work=no, Supporting protocol for DeviceNet Safety=no, Supporting protocol for INTERBUS-Safety=no, Supporting protocol for PROFIsafe=no, Supporting protocol for SafetyBUS p=no, Supporting protocol for other bus systems=yes, Radio standard Bluetooth=no, Radio standard Wi-Fi 802.11=no, Radio standard GPRS=no, Radio standard GSM=no, Radio standard UMTS=no, IO link master=no, System accessory=yes, Degree of protection (IP)=IP20, Number of slots=1, With pluggable modules, digital I/O=yes, With pluggable modules, analogue I/O=yes, With pluggable modules, communication modules=yes, With pluggable modules, function and technology modules=yes, With pluggable modules, central modules=yes, With pluggable modules, others=yes, Type of electric connection=Spring clamp connection, With potential separation=yes, Fieldbus connection over separate bus coupler possible=no, With bus coupler for modular station connection=yes, Rail mounting possible=yes, Wall mounting/direct mounting=no, Front built-in possible=no, Rack-assembly possible=no, Suitable for safety functions=no, Appendant operation agent (Ex ia)=no, Appendant operation agent (Ex ib)=no, Explosion safety category for gas=ATEX gas-ex-protection, Cat. 3G, Explosion safety category for dust=ATEX dust-ex-protection, Cat. 3D, Width=51 mm, Height=65 mm, Depth=100 mm

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

