


**Fieldbus coupler Interbus ECO 500KB - Fieldbus basic device DC24V 750-344**

**WAGO**  
750-344  
4017332790352 EAN/GTIN

**1718,63 CNY** excl. VAT\*\*  
plus shipping


15-16 days\* (CHN)

With integrated power supply=yes, Input voltage at DC=24 V, Type of voltage (input voltage)=DC, Max. input current DC=0,26 A, Number of HW-interfaces other=2, With optical interface=no, Supporting protocol for TCP/IP=no, Supporting protocol for PROFIBUS=no, Supporting protocol for CAN=no, Supporting protocol for INTERBUS=yes, Supporting protocol for ASI=no, Supporting protocol for KNX=no, Supporting protocol for MODBUS=no, Supporting protocol for Data-Highway=no, Supporting protocol for DeviceNet=no, Supporting protocol for SUCONET=no, Supporting protocol for LON=no, Supporting protocol for SERCOS=no, Supporting protocol for PROFINET IO=no, Supporting protocol for PROFINET CBA=no, Supporting protocol for Foundation Fieldbus=no, Supporting protocol for EtherNet/IP=no, Supporting protocol for AS-Interface Safety at Work=no, Supporting protocol for DeviceNet Safety=no, Supporting protocol for INTERBUS-Safety=no, Supporting protocol for PROFIsafe=no, Supporting protocol for SafetyBUS p=no, Supporting protocol for other bus systems=no, Radio standard Bluetooth=no, Radio standard Wi-Fi 802.11=no, Radio standard GPRS=no, Radio standard GSM=no, Radio standard UMTS=no, IO link master=no, System accessory=yes, Degree of protection (IP)=IP20, Number of slots=1, With pluggable modules, digital I/O=yes, With pluggable modules, analogue I/O=yes, With pluggable modules, communication modules=yes, With pluggable modules, function and technology modules=yes, With pluggable modules, central modules=yes, With pluggable modules, others=yes, Type of electric connection=Spring clamp connection, With potential separation=yes, Fieldbus connection over separate bus coupler possible=no, With bus coupler for modular station connection=yes, Rail mounting possible=yes, Wall mounting/direct mounting=no, Front built-in possible=no, Rack-assembly possible=no, Suitable for safety functions=no, Appendant operation agent (Ex ia)=no, Appendant operation agent (Ex ib)=no, Explosion safety category for gas=ATEX gas-ex-protection, Cat. 3G, Explosion safety category for dust=ATEX dust-ex-protection, Cat. 3D, Width=50 mm, Height=65 mm, Depth=97 mm

**YOUR ADVANTAGES**

**WORLDWIDE TRADE**  
Corporate video eibmarkt®

**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide

**DHL TRACK & TRACE**  
Shipment tracking

**COMPLAINTS HANDLING**  
Obliging and 100% safely

**25 YEARS OF EXPERIENCE**  
In worldwide mail order

**ORDER LIVE CHAT**  
With order history

**SHORT DELIVERY TIME**  
Warehousing

**REFUND**  
Within 14 days

**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online
