



Analog input terminal 2-channel 0-20mA diff. - Fieldbus analogue module 2 In / 0 Out 750-480


WAGO

750-480

4045454905293 EAN/GTIN

2153,03 CNY excl. VAT**
plus shipping



15-16 days* (CHN)

Supply voltage DC=24 V, Voltage type of supply voltage=DC, Input, current=yes, Input, voltage=no, Input, resistor=no, Input, resistance thermometer=no, Input, thermocouple=no, Input signal, configurable=no, Resolution of the analogue inputs=12 Bit, Output, current=no, Output, voltage=no, Output signal configurable=no, Number of analogue inputs=2, Analogue inputs configurable=no, Analogue outputs configurable=no, Supporting protocol for TCP/IP=no, Supporting protocol for PROFIBUS=no, Supporting protocol for CAN=no, Supporting protocol for INTERBUS=no, Supporting protocol for ASI=no, Supporting protocol for KNX=no, Supporting protocol for MODBUS=no, Supporting protocol for Data-Highway=no, Supporting protocol for DeviceNet=no, Supporting protocol for SUCONET=no, Supporting protocol for LON=no, Supporting protocol for PROFINET IO=no, Supporting protocol for PROFINET CBA=no, Supporting protocol for SERCOS=no, Supporting protocol for Foundation Fieldbus=no, Supporting protocol for EtherNet/IP=no, Supporting protocol for AS-Interface Safety at Work=no, Supporting protocol for DeviceNet Safety=no, Supporting protocol for INTERBUS-Safety=no, Supporting protocol for PROFIsafe=no, Supporting protocol for SafetyBUS p=no, Supporting protocol for other bus systems=no, Radio standard Bluetooth=no, Radio standard Wi-Fi 802.11=no, Radio standard GPRS=no, Radio standard GSM=no, Radio standard UMTS=no, IO link master=no, System accessory=yes, Degree of protection (IP)=IP20, Type of electric connection=Spring clamp connection, Fieldbus connection over separate bus coupler possible=yes, Rail mounting possible=yes, Wall mounting/direct mounting=no, Front built-in possible=no, Rack-assembly possible=no, Suitable for safety functions=no, Appendant operation agent (Ex ia)=no, Appendant operation agent (Ex ib)=no, Explosion safety category for gas=ATEX gas-ex-protection, Cat. 3G, Explosion safety category for dust=ATEX dust-ex-protection, Cat. 3D, Width=12 mm, Height=64 mm, Depth=100 mm

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


COMPLAINTS HANDLING

Obliging and 100% safely


SHORT DELIVERY TIME

Warehousing


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


25 YEARS OF EXPERIENCE

In worldwide mail order


REFUND

Within 14 days


DHL TRACK & TRACE

Shipment tracking


ORDER LIVE CHAT

With order history


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

