Item Number
EB10764238

29.03.2024/00:37

https://www.eibabo.cn/wago/digital-output-terminal-4-channel-5vdc-20ma-fieldbus-digital-module-0-in-4-out-750-519-eb10764238



Digital output terminal 4-channel 5VDC 20mA - Fieldbus digital module 0 In / 4 Out 750-519

WAGO
750-519
4045454848446 EAN/GTIN

535,41 CNY excl. VAT**

plus **shipping**

15-16 days* (CHN)

Supply voltage DC=24 V, Voltage type of supply voltage=DC, Number of digital outputs=4, Digital inputs configurable=no, Digital outputs configurable=no, Type of digital output=Other, Output current=0,002 A, Permitted voltage at output=5 V, Type of output voltage=DC, Short-circuit protection, outputs available=no, With optical interface=no, Supporting protocol for TCP/IP=no, Supporting protocol for PROFIBUS=no, Supporting protocol for CAN=no, Supporting protocol for INTERBUS=no, Supporting protocol for ASI=no, Supporting protocol for KNX=no, Supporting protocol for MODBUS=no, Supporting protocol for Data-Highway=no, Supporting protocol for DeviceNet=no, Supporting protocol for SUCONET=no, Supporting protocol for LON=no, Supporting protocol for PROFINET IO=no, Supporting protocol for PROFINET CBA=no, Supporting protocol for SERCOS=no, Supporting protocol for Foundation Fieldbus=no, Supporting protocol for EtherNet/IP=no, Supporting protocol for AS-Interface Safety at Work=no, Supporting protocol for DeviceNet Safety=no, Supporting protocol for INTERBUS-Safety=no, Supporting protocol for PROFIsafe=no, Supporting protocol for SafetyBUS p=no, Supporting protocol for other bus systems=yes, Radio standard Bluetooth=no, Radio standard Wi-Fi 802.11=no, Radio standard GPRS=no, Radio standard GSM=no, Radio standard UMTS=no, IO link master=no, System accessory=yes, Degree of protection (IP)=IP20, Type of electric connection=Spring clamp connection, Fieldbus connection over separate bus coupler possible=yes, Rail mounting possible=yes, Wall mounting/direct mounting=no, Front built-in possible=no, Rack-assembly possible=no, Suitable for safety functions=no, Appendant operation agent (Ex ia)=no, Appendant operation agent (Ex ib)=no, Explosion safety category for gas=None, Explosion safety category for dust=None, Width=12 mm, Height=73 mm, Depth=100 mm

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

COMPLAINTS HANDLING
Obliging and 100% safely

SHORT DELIVERY TIME
Warehousing

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

25 YEARS OF EXPERIENCE
In worldwide mail order

REFUND
Within 14 days

DHL TRACK & TRACE
Shipment tracking

ORDER LIVE CHAT
With order history

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online