Pulse width output terminal 2-channel 24VDC 0.1A - Fieldbus function-/technology module 750-511/0...

WAGO
750-511/000-002
4045454831608 EAN/GTIN

1549,44 CNY excl. VAT**

plus **shipping**

🚚 15-16 days* (CHN)

Supply voltage DC=24 V, Voltage type of supply voltage=DC, With optical interface=no, Supporting protocol for TCP/IP=no, Supporting protocol for PROFIBUS=no, Supporting protocol for CAN=no, Supporting protocol for INTERBUS=no, Supporting protocol for ASI=no, Supporting protocol for KNX=no, Supporting protocol for MODBUS=no, Supporting protocol for Data-Highway=no, Supporting protocol for DeviceNet=no, Supporting protocol for SUCONET=no, Supporting protocol for LON=no, Supporting protocol for PROFINET IO=no, Supporting protocol for PROFINET CBA=no, Supporting protocol for SERCOS=no, Supporting protocol for Foundation Fieldbus=no, Supporting protocol for EtherNet/IP=no, Supporting protocol for AS-Interface Safety at Work=no, Supporting protocol for DeviceNet Safety=no, Supporting protocol for INTERBUS-Safety=no, Supporting protocol for PROFIsafe=no, Supporting protocol for SafetyBUS p=no, Supporting protocol for other bus systems=yes, Radio standard Bluetooth=no, Radio standard Wi-Fi 802.11=no, Radio standard GPRS=no, Radio standard GSM=no, Radio standard UMTS=no, IO link master=no, System accessory=yes, Suitable for counting=no, Suitable for weighing=no, Suitable for temperature control=no, Suitable for welding control=no, Suitable for pressure control=no, Suitable for NC=no, Suitable for electronic positioning=no, Suitable for CNC=no, Suitable for SSI=no, Suitable for incremental data detection=no, Suitable for detection absolute value=no, Suitable for flux controller=no, Suitable for flux measurement=no, Suitable for path controller=no, Suitable for cam controller=no, Suitable for flying saw=no, Suitable for multi-axis control=no, Suitable for single-axis controller=no, Suitable for multi-axis positioning=no, Suitable for single-axis positioning=no, Function block restart blockage=no, Function block automatic reset=no, Contactor control function block=no, Function block emergency stop=no, Function block contactless working protection installation=no, Function block affirm pushbutton=no, Function block 2-hand switching=no, Function block operating mode selection=no, Function block access control=no, Degree of protection (IP)=IP20, Fieldbus connection over separate bus coupler possible=yes, Frequency measurement=no, Rail mounting possible=yes, Wall mounting/direct mounting=no, Front built-in possible=no, Rack-assembly possible=no, Suitable for safety functions=no, Appendant operation agent (Ex ia)=no, Appendant operation agent (Ex ib)=no, Explosion safety category for gas=None, Explosion safety category for dust=None, Width=12 mm, Height=64 mm, Depth=100 mm

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee