



Storage - Boiler electric SH 10 SL



Stiebel Eltron

SH 10 SL

229475

4017212294758 EAN/GTIN

4164,61 CNY excl. VAT**

plus shipping



4-5 days* (CHN)

Storage tank SH 10 SL energy efficiency class A, energy efficiency class spectrum A to G, material of the boiler steel, material jacket plastic, volume of the container 10l, nominal power 2kW, connection voltage 230 ... 230V, frequency 50 Hz, version above table, applicable with normal water pressure, Warm-up time from 10 °C - 65 °C 18 min, tapping capacity at 60 °C, continuous operation 10 l/min, wall installation, vertical placement, temperature limitation, max. permissible operating pressure 7 bar, protective anode, height 503 mm, width 295 mm, depth 275 mm, connection for cold drinking water external thread, nominal inside diameter cold drinking water 1/2 inch (15), pipe outside diameter cold drinking water 21.3mm, connection hot water external thread, nominal inside diameter hot water connection 1/2 inch (15), pipe outside diameter hot drinking water 21.3mm, protection class (IP) IP24, energy efficiency hot water 37%, tapping profile XXS, APPLICATION: The SH storage tanks are suitable for the hot water supply of several tapping points. Flameproof device for use with pressure fittings. Installation only with appropriate security group. Device variant with 3.3 kW connected load for faster heating. EQUIPMENT AND COMFORT: The solutions for decentralized group supply. Energy and water losses due to long pipe runs are avoided. Low energy losses thanks to high-quality thermal insulation. Temperature controller with temperature measurement directly in the water Stepless temperature selection from 35°C-85°C. Temperature limitation at 38°C, 45°C, 55°C and 65°C and automatic frost protection when the device is switched off. Heat-up indication by signal lamp. Pressure-resistant copper tank with high-quality EPS thermal insulation. INSTALLATION AND SERVICE: Installation system for quick assembly. Simple replacement by considering commercially available attachment points. Easy wall mounting with mounting strip. Mounting template included. metal water connections. Suitable safety groups as accessories. Connection cable with protective contact plug. Practical cable depot in the back of the device for holding excess lengths of the connection cable Protection class IP 24 SAFETY AND QUALITY: Copper tubular heating element with low surface load. Resettable safety temperature limiter Mechanical temperature limitation as scalding protection at 38°C or 45°C.

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

