

## Item Number EB14200843

https://www.eibabo.cn/stiebel-eltron/wall-tank-30l-1-6-kw-white-boiler-electric-shz-30-lcd-eb14200843



Wall tank 30I, 1-6 kW, white - Boiler electric SHZ 30 LCD

×

**Stiebel Eltron**SHZ 30 LCD
231251
4017212312513 EAN/GTIN

6327,55 CNY excl. VAT\*\*

plus **shipping bulky item** 



15-16 days\* (CHN)

Wall-mounted storage tank 30l, 1-6 kW, white SHZ 30 LCD Energy efficiency class A, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the container 30l, nominal output 6kW, connection voltage 230... 400V, three-phase version, frequency 50 /60 Hz, hanging version, with off-peak mode, can be used with normal water pressure, warm-up time from 10 °C - 65 °C 18 min, tapping capacity at 60 °C, continuous operation 18 l/min, wall installation, vertical placement, with temperature display, temperature limitation, max. permissible Operating pressure 6 bar, with thermometer, protective anode, height 770 mm, width 410 mm, depth 420 mm, cold drinking water external thread connection, nominal inside diameter of cold drinking water 1/2 inch (15), pipe outside diameter of cold drinking water 21.5 mm, hot water external thread connection, nominal inside diameter of hot water connection 1/2 inch (15), pipe outer diameter for warm drinking water 21.5 mm, connection tap connection internal thread, nominal inner diameter tap connection 1/2 Inch (15), pipe outer diameter drain connection 21.5mm, protection class (IP) IP25, energy efficiency hot water 38%, tapping profile S, SHZ LCD hot water wall storage tank for any desired hot water supply. Closed (pressure-resistant) or open (unpressurized) to supply several or one tapping point. Installation in conjunction with plastic pipe systems possible (observe manufacturer information and application limits). Electronic hot water temperature control. Depending on the controller and the selected operating mode, the water content is kept at the set temperature. Stepless setting from 20 degrees C to 85 degrees C. Maximum energy efficiency with 3 selectable automatic ECO functions: ECO Comfort, ECO Plus and ECO Dynamic and optional reverse control in dual circuit operation. Control panel with function keys and LCD display. Menu selection and display supported by backlighting: Temperature setting and display to the degree, temperature limitation to the degree (40 to 60 degrees C), heat content display in liters of mixed water volume (40 degrees C), optional energy consumption display, automatic calcification display, service and error display, heating operating display. Active corrosion protection through maintenance-free impressed current anode. Steel inner container with special direct enamel "anticor". Thermal insulation with minimal heat loss. Universal copper heating flange for dual/single circuit operation/boiler operation. Power setting, operating mode selection (dual circuit, single circuit, boiler) and activation of reverse control...

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

