×



Item Number EB14208400

https://www.eibabo.cn/stiebel-eltron/wall-storage-tank-white-30l-white-boiler-electric-hfa-z-30-eb14208 400



Wall storage tank white 30L white - Boiler electric HFA-Z 30

Stiebel Eltron

HFA-Z 30 073111 4017210731118 EAN/GTIN

5093,73 CNY excl. VAT**

plus shipping bulky item



4-5 days* (CHN)

Wall storage tank ws 30L white HFA-Z 30 energy efficiency class B, energy efficiency class spectrum A to G, boiler material steel, jacket material steel, volume of the container 30l, nominal output 6kW, connection voltage 230 ... 400V, three-phase version, frequency 50 Hz, hanging version, With off-peak mode, can be used with normal water pressure, warm-up time from 10 °C - 65 °C 18 min, tapping capacity at 60 °C, continuous operation 18 l/min, wall installation, vertical placement, temperature limitation, max. permissible operating pressure 6 bar, protective anode, height 770 mm, width 410 mm, depth 420 mm, cold drinking water connection male thread, nominal inside diameter cold drinking water 1/2 inch (15), pipe outside diameter cold drinking water 21.5 mm, connection Tap connection female thread, tap connection nominal inside diameter 1/2 inch (15), pipe outside diameter varm drinking water 21.5 mm, connection Tap connection female thread, tap connection nominal inside diameter 1/2 inch (15), pipe outside diameter drain connection 21, 5mm, degree of protection (IP) IP24, energy efficiency hot water 36%, tapping profile S, hot water wall storage tank for any desired hot water supply. -Closed (pressure-resistant) to supply several tapping points. Installation also in connection with plastic pipe systems (observe manufacturer's information and application limits). -Open (non-pressurized) to supply a tapping point. - Boiler operation also possible. Steel inner container with special enamel and anti-corrosion rod, thermal insulation with low heat loss. Heating flange dual circuit/single circuit operation. The water content is kept at the set temperature depending on the controller (depending on the selting from approx. 35 degrees C to approx. 82 degrees C possible. Automatic frost protection for single-circuit operation. Signal lamp for boiler operation and rapid heating (once by push button, remote control on site), exchangeable copper heating flange with drain connection. Installation with: Safety group KV 30 o

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide







DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

