



**Roller lever metal housing - Square roller lever switch
IP67 LSM-11D/L**



Eaton
LSM-11D/L
266150
4015082661502 EAN/GTIN

520,20 CNY excl. VAT**
plus shipping

 15-16 days* (CHN)

Roller lever metal housing LSM-11D/L sensor width 31mm, sensor diameter 0mm, sensor height 61mm, sensor length 33.5mm, rated operational current Ie at AC-15, 24 V 6A, rated operational current Ie at AC-15, 125 V 6A, rated operational current Ie at AC-15, 230 V 6A, rated operational current Ie at DC-13, 24 V 3A, rated operational current Ie at DC-13, 125 V 0.8A, rated operational current Ie at DC-13, 230 V 0.3A, switching function Slow-action switching element, positive opening, number of safety-related auxiliary contacts 0, number of contacts as NC contacts 1, number of contacts as NO contacts 1, number of contacts as change-over contacts 0, version of the interface without, version of the interface for safety-related communication without, cuboid housing design, housing material metal, coating housing other, design of the actuating element angle roller lever, alignment of the actuating element other, design of the electrical connection cable entry (metric), Suitable for safety functions, explosion protection category for gas without, explosion protection category for dust without, ambient temperature during operation 25 ... 70°C, degree of protection (IP) IP67, degree of protection (NEMA) 4X, safety position switch, basic function: position switch, safety Position switch, type code: LS(M)-..., range: roller lever, degree of protection: IP66, IP67, equipment: complete device, ambient temperature: -25 - +70 °C, description: long, contact configuration NO = NO: 1 NO, contact configuration NC = NC contact: 1 NC, note: = safety function, through positive opening according to IEC/EN 60947-5-1, positive opening (ZW): yes, housing cover color: yellow, housing: metal, connection type: cage clamp, cage clamp is a registered Trademarks of the company Wago Kontakttechnik, 32432 Minden., Accessories for the cage-clamp connection from the company Wago: insertion bridge, grey, Wago order no. 264-402, standards and regulations: IEC/EN 60947

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

