×



https://www.eibabo.cn/brumberg/led-wall-light-1w-230v-led-wws-orientation-luminaire-1-2w-0r3941ww-eb11542284



## LED wall light 1W/230V LED wws - Orientation luminaire 1,2W 0R3941WW

**Brumberg** 

0R3941WW 4250047758327 EAN/GTIN

**737,65 CNY** excl. VAT\*\*

plus **shipping** 



15-16 days\* (CHN)

LED wall light 1W/230V LED wws 0R3941WW, illuminant=LED not interchangeable, with illuminant=yes, suitable for number of illuminants=1, material of the housing=stainless steel, color of the housing=white, type of cover=pane, material of the cover=opal plastic, Suitable for surface mounting=no, type of voltage=AC, nominal voltage=230 V, control gear=LED control gear current-controlled, with control gear=yes, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX =no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwitch=no, dimming manufacturer-specific=no, dimming mains voltage modulation=no, dimming trailling edge=no, dimming leading edge=no, dimming programmable=no , RF dimming=no, Sine Wave Reduction dimming=no, Touch and Dim dimming=no, Zigbee dimming=no, dimming with push-button=no, dimming dependent on operating device=no, without dimming function=yes, degree of protection (IP)= IP20, protection class=I, suitable for lamp power ng=1.2 W, rated luminous flux according to IEC 62722-2-1=40 Im, light color=white, color temperature=3000 K, color rendering index CRI=80-89, diameter=85 mm, installation height/depth=65 mm, installation diameter= 68 mm, LED recessed wall light, white, round. Recessed mounting, wall mounting. R3941WW: incl. converter for connection to 230 V mains voltage, switchable, and cavity wall mounting box Ø DA: 68 mm / installation depth: 65 mm. Socket: without, mounting type: built-in mounting, mounting location: wall mounting, material: stainless steel / acrylic / plastic, protection class: according to DIN EN 60529: IP20, protection class: (EN 61140) I, voltage: 230V AC 50Hz, power: 1.2W, number of bulbs / sockets: 1.0 pieces, luminous flux: 40Im, color temperature: 3000K, light color: white, with control gear, type of dimming: switchable.

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®




COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

