

Item Number EB11600098

https://www.eibabo.cn/maico/fan-two-way-industrial-fan-300mm-ezf-30-6-b-eb11600098



Fan - Two-way industrial fan 300mm EZF 30/6 B



Maico

EZF 30/6 B 0085.0053 4012799850533 EAN/GTIN

5802,49 CNY excl. VAT**

plus shipping



15-16 days* (CHN)

Fan EZF 30/6 B mains frequency 50Hz, rated voltage 230V, conveyor temperature -20... 60°C, volume flow 1100m³/h, speed 9301/min, protection class (IP) IP55, ventilation version, nominal width 300mm, shutter without, For flush mounting. Installation possible in any position. Wall sleeve made of galvanized sheet steel. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Plastic protective grille on the suction side, pearl white, contact protection in accordance with DIN EN ISO 13857. Conveying direction: The following figure shows the conveying direction. Conveying direction A: Suctioning via the motor, standard, Conveying direction B: Blowing via the motor, available on request, direction of rotation, reversing operation: The volume flow decreases by approx. 35% with an abnormal conveying direction. Motor: asynchronous motor. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. AC motor: EZF series. Rated voltage 230 V, 50 Hz. Thermal overload protection as standard. Fans.. /B: Capacitor motors with operating capacitor on the protective grille or on the wall sleeve. Protection class IP 55. Fans.. /D: Capacitor motors with operating capacitor in the connection box. Protection class IP 54. Fans.. /E: Shaded pole motors, not reversible. Protection class IP 54. Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: With free suction, the fan may only be put into operation if the impeller is protected against contact in accordance with DIN EN ISO 13857. Article: EZF 35/4 B, version: wall sleeve, delivery volume: 2760 m3/h, nominal delivery volume: 1938 m3 /h / in opt. Efficiency, pressure pfs, nominal: 57 Pa - in opt. Efficiency, speed nnominal: 1455 1/min - in opt. Efficiency, speed: 1461 1/min, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: alternating current, rated voltage:

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUNDWithin 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

