×



## Item Number EB11600731

https://www.eibabo.cn/maico/axial-wall-fan-wall-plate-dn-350-two-way-industrial-fan-350mm-dzq-35-4-b-eb11600731



## Axial wall fan wall plate DN 350 - Two-way industrial fan 350mm DZQ 35/4 B

**Maico**DZQ 35/4 B
0083.0123
4012799831235 EAN/GTIN

5617,20 CNY excl. VAT\*\*

plus **shipping** 



15-16 days\* (CHN)

Axial wall fan wall plate DN 350 DZQ 35/4 B mains frequency 50Hz, rated voltage 400V, conveying medium temperature 60 ... 60°C, volume flow 1950m³/h, speed 14101/min, protection class (IP) IP55, ventilation and ventilation version, nominal width 350mm, closing flap without, protective grille on the suction side, yellow chromated, contact protection in accordance with DIN EN ISO 13857. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Installation possible in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction A: Suction via the motor, standard. Conveying direction B: Blowing via the motor, on request. Direction of rotation, reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. Three-phase motor: DZQ and DZS series. Rated voltage 400 V, 50 Hz. Protection class IP 55. Exception DZQ/DZS... D IP 54. Thermal overload protection as standard. Exception: Available on request for DZQ/DZS 25/4 D and pole-changing axial wall fans. The connections are potential-free on terminals and must be connected to a full motor protection switch, e.g. MV 25, or the control circuit of a contactor. Polechanging fans: Ensure overload protection with a full motor protection switch to be provided on site. Pole-changing motors with speed ratios of 8/4 or 4/2 are connected using the Dahlander principle. Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: The fan may only be put into operation if the impeller is protected against contact in accordance with DIN EN ISO 13857. Article: DZQ 35/4 B, design: square wall plate, delivery volume: 2840 m3/h, nominal delivery volume: 1950 m3/h / in opt. Efficiency, pressure pfs, nominal: 70 Pa - in opt. Efficiency, speed nnominal: 1380 1/min - in opt. Efficiency, speed: 1410 1/min, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: three-phase current, rated voltage: 400 V, mains frequency: 50 Hz, nominal power: 133 W / in opt. Efficiency, Irated: 0.35 A / in opt. Efficiency, IMax: 0.4 A, protection class: IP 55, thermal class: B, power supply cable: 7 / 1.5 mm2, installation location: wall / ceiling, installation type: surface-mounted, installation position; horizontal / vertical, material; sheet...

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



**25 YEARS OF EXPERIENCE** *In worldwide mail order* 



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product

before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

