

Item Number EB11601201

×

https://www.eibabo.cn/maico/axial-wall-fan-steel-wall-ring-dn-300-two-way-industrial-fan-300mm-ezs-3 0-6-b-eb11601201



Axial wall fan steel wall ring DN 300 - Two-way industrial fan 300mm EZS 30/6 B

Maico EZS 30/6 B 0094.0002 4012799940029 EAN/GTIN

6006,07 CNY excl. VAT**

plus shipping bulky item

here a state in the second sec

Axial wall fan steel wall ring DN 300 EZS 30/6 B mains frequency 50Hz, rated voltage 230V, medium temperature 60 ... 60°C, volume flow 1200m³/h, speed 9301/min, protection class (IP) IP55, design ventilation, nominal width 300mm , flap without, protective grille on the suction side, yellow chromated, protection against accidental contact according to DIN EN ISO 13857. 8-bladed impellers made of glass fiber reinforced polyamide. Dynamically balanced on 2 levels, according to quality level 6.3, DIN ISO 1940, Part 1. Can be installed in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction of student. Conveying direction B: blowing via the motor, on request. Direction of rotation, reverse operation: The volume flow is reduced by approx. 35% if the direction of flow is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: fans with shaded-pole motor (...-E). Not suitable for pumping water vapor-saturated air. AC motor: Type series EZQ and EZS. Rated voltage 230 V, 50 Hz. Thermal overload protection as standard. Fans ../B: Capacitor motors with operating capacitor on the protective grille or on the wall sleeve, protection class IP 55. Fans ../D: Capacitor motors with operating capacitor in the connection box, protection class IP 54. Fans ../E: Shaded-pole motors, not reversible, protection class IP 54. Electrical connection: To the terminal block in the end cover of the motor. Safety instructions: The fan may only be put into operation if the contact protection of the impeller is guaranteed in accordance with DIN EN ISO 13857. Item: EZS 30/6 B, design: steel wall ring, delivery volume: 1200 m3/h, speed: 930 rpm, impeller type: axial, speed controllable: yes, reversibility: yes, type of voltage: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, nominal power: 60 W, Irated: 0.32 A, IMax: 0.35 A, protection class: IP 55, insulation class: B, installation loca

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

