×



## Item Number EB13302681

https://www.eibabo.cn/ceag/led-self-contained-light-with-autom.-funct.test-emergency-luminaire-7w-ip6 5-1...8h-outdoor-wall...-eb13302681



LED self-contained light with autom. funct.test - Emergency luminaire 7W IP65 1...8h Outdoor Wall...

## Ceag

Outdoor Wall CGLine+ 40071354874 4012539344483 EAN/GTIN

2779,45 CNY excl. VAT\*\*

plus shipping



15-16 days\* (CHN)

LED self-contained light with autom. Funkt.test Outdoor Wall CGLine+ Mounting type Wall mounting, Escape route lighting function, Suitable for marking type other, Type of marking not applicable, Monitoring device Monitoring module (centrally supplied system), Switching type maintained/standby mode, With remote switch connection, Infeed decentralized (individual battery), Battery properties lithium-ion, Light source LED not interchangeable, With light source, Other socket, Number of lamp heads 1, Housing material aluminium, Housing color grey, Cover material transparent plastic, Type of voltage AC, Nominal voltage 220 ... 240V, Control gear LED control gear current-controlled, Light distributor focus lens, Energy efficiency class of the built-in illuminant A++, A+, A (LED), rated service life L70/B50 at 25 °C 50000h, degree of protection (IP) IP65, impact resistance IK10, protection class I, luminaire with limited surface temperature "D mark", rated ambient temperature according to IEC6 2722-2-1 5 ... 35°C, max. system power 7W, rated luminous flux according to IEC 62722-2-1 225lm, color temperature 6500 ... 6500K, power factor 0.91, nominal operating time 1 ... 8h, width 184mm, Height/depth 160mm, length 303mm, type of wiring suitable for through-wiring, number of poles 6, conductor cross-section 2.5mm², connection type plug-in connection, self-contained light for self-sufficient operation (incl. colored LED for differentiated status display) or for connection to the central monitoring device CGLine+. Automatic function test (weekly) and automatic duration test (every 6 months) can optionally be switched off with a reminder of due BT after 12 months. Manual function test or duration test triggered by magnet. Freely selectable operating time for emergency lighting: 1 h, 3 h or 8 h, long service life of 50,000 h, 1 minute switch-back delay after power is restored. Blocking function via central monitoring device for company idle times. Permissible temperature range: permanent light -5°C to +30°C / non-maintained light 0°C to +35°C. Inclined light emission to illuminate the escape route along the wall. Light control using double lens technology. Asymmetrical optics for particularly efficient escape route illumination. Type of installation: wall mounting Illuminant: LED lamp output: 7.0 W Housing material: aluminum Housing colour: gray Cover material: transparent plastic Type of marking: not applicable Monitoring device: automatic self-test Ball-proof: no Switching type: maintained/standby mode With remote switch connection (VDE 0100-718, VDE 0108-100): Yes Power supply: decentralized (individual...

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

