

Item Number EB15701604

×

https://www.eibabo.cn/abb/circuit-breaker-16a-k-1p-miniature-circuit-breaker-1-p-k16a-s401m-k16-eb1 5701604

Circuit breaker 16A K 1p - Miniature circuit breaker 1-p K16A S401M-K16

ABB S401M-K16 2CCS571001R0467 7612270101702 EAN/GTIN

199,55 CNY excl. VAT**

plus shipping



Circuit breaker 16A K 1p S401M-K16 tripping characteristic K, number of poles (total) 1, number of fused poles 1, rated current 16A, rated voltage 400V, rated insulation voltage Ui 440V, rated impulse withstand voltage Uimp 4kV, rated switching capacity lon according to EN 60898 at 230 V 10kA, rated switching capacity lon according to IEC 60947-2 at 230 V 25kA, rated switching capacity lon according to IEC 60947-2 at 400 V 10kA, rated switching capacity lon according to IEC 60947-2 at 230 V 25kA, rated switching capacity lon according to IEC 60947-2 at 400 V 10kA, rated switching capacity lon according to IEC 60947-2 at 230 V 25kA, rated switching capacity lon according to IEC 60947-2 at 400 V 10kA, rated switching capacity lon according to IEC 60947-2 at 230 V 25kA, rated switching capacity lon according to IEC 60947-2 at 400 V 10kA, type of voltage AC, frequency 50 ... 50Hz, energy limitation class 3, overvoltage category 3, degree of pollution 3, additional equipment possible, width in pitch units 1, installation depth 75mm, degree of protection (IP) IP20, ambient temperature during operation -25 ... 55°C, connectable conductor cross-section solid 0.8 ... 25mm², the S 400 series circuit breakers protect cables and lines against overload and short circuit according to DIN VDE 0100-430 and DIN VDE 0100-530. They meet the building regulations DIN VDE 0641-11 or IEC/EN 60898-1, DIN VDE 0660-101 or IEC/EN60947-2. Its patented connection terminal ensures simple and safe contacting and handling by means of a pressure plate. Conductor cross-sections up to 35 mm² can be connected directly to the device via the connection terminal with insulation in protection class IP20. Contact is made directly via the socket system and the outer conductor contact can be freely selected (L1, L2 or L3). The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the S 400 fit for worldwide use. Before delivery, each device is subjected to three intensive tests for quality

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

