

SIEMENS

onDel->currentur del J¢Del/I ¢ Del->

3UG4622-1AW30

over delay

Item Number EB10767032

×

https://www.eibabo.cn/siemens/monitoring-relay-from-0.1-10a-ac-dc-3ug4622-1aa30-eb10767032

Monitoring relay from 0.1 - 10A AC/DC 3UG4622-1AA30

Siemens 3UG4622-1AA30 4011209642416 EAN/GTIN

849,01 CNY excl. VAT**

plus shipping



Monitoring relay from 0.1 - 10A AC/DC 3UG4622-1AA30 Design of the electrical connection Screw connection, With removable terminals, 1-phase undercurrent possible, 1phase overcurrent possible, Includes DC voltage undercurrent function, Includes DC voltage overcurrent function, DC current window, rated control supply voltage Us at AC 50 Hz 20.4 ... 26.4V, rated control supply voltage Us at AC 60 Hz 20.4 ... 26.4V, rated control supply voltage Us at DC 20.4 ... 26.4V, type of voltage for AC/DC actuation, current measuring range 0.05 ... 15A, min. adjustable response delay time 0.1s, max. permissible response delay time 20s, min. adjustable off-delay time 0.1s, max of contacts as NO contact 0, number of contacts as changeover contact 1, width 22.5 mm, height 92 mm, depth 91 mm, digital monitoring relay, current monitoring, 22.5 mm from 0.05-10 A AC/DC overshoot and undershoot supply voltage: AC/DC 24 V DC and AC 50 to 60 Hz without electrical isolation from the measuring circuit Start-up and interference peak delay. 0.1 to 20 s hysteresis 0.01 to 5 A 1 changeover contact with or without fault memory Screw connection Successor product for 3UG3522-1AC.. SIRIUS 3UG4 digitally adjustable current monitoring relay for monitoring currents for overshoot and undershoot, e.g. B. to ensure the functionality of electrical consumers or to monitor wire breaks. Worldwide use thanks to international certificates. The relay can be variably set to overshoot or window monitoring. Delay times and RESET behavior can be freely parameterized. Less space required in the control cabinet thanks to a narrow overall width. Reliable diagnostics by displaying the actual value and status messages. All versions with removable connection terminals. In addition to screw connection technology, the devices are also available with spring-loaded connections for a quick, maintenance-free and vibration-proof connection. They are also available in different voltages, optionally with IO-Link. The comprehensive range of accessories, such as device identif

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

