

Item Number EB15702121

×

https://www.eibabo.cn/abb/circuit-breaker-k-6ka-16a-3p-na-miniature-circuit-breaker-4-p-k16a-s203-k1 6na-eb15702121



Circuit breaker K,6kA,16A,3P+NA - Miniature circuit breaker 4-p K16A S203-K16NA

ABB

S203-K16NA 2CDS253103R0467 4016779532716 EAN/GTIN

823,37 CNY excl. VAT**

plus shipping



Automatic circuit breaker K,6kA,16A,3P+NA S203-K16NA Tripping characteristic K, number of poles (total) 4, number of fused poles 3, rated current 16A, rated voltage 400V, rated insulation voltage Ui 440V, rated impulse withstand voltage Uimp 4kV, rated switching capacity Icn according to EN 60898 at 230 V 6kA, rated switching capacity Icn according to EN 60898 at 400 V 6kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 20kA, rated switching capacity Icu according to IEC 60947-2 at 400 V 10kA, type of voltage AC, frequency 50 ... 60Hz, energy limitation class 3, active switching Neutral conductor, overvoltage category 3, degree of pollution 3, additional equipment possible, width in pitch units 4, mounting depth 69mm, degree of protection (IP) IP20, ambient temperature during operation -25 ... 55°C, connectable conductor cross-section stranded 0 ... 25mm², connectable conductor cross-section solid 0 ... 35mm², The automatic circuit breakers of the S 200 series protect cables and lines from overload and short circuits according to DIN VDE 0100-430 and DIN VDE 0100-530. They meet the building regulations DIN VDE 0641-11 or IEC/EN 60898-11, DIN VDE 0660-101 or IEC/EN60947-2 and UL 1077. Its patented connection terminal ensures simple and safe contacting and handling by means of a pressure plate. For better visibility when wiring, the connection opening for cables is above the connection opening for the busbar. Conductor cross-sections up to 35 mm² can be connected directly to the device via the connection terminal with insullation in protection class IP20. The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the S 200 fit for worldwide use. Before delivery, each device is subjected to three intensive tests for quality and performance.

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

