



Recessed light round 12V GX5.3 50W - Downlight 1x0...50W 620 014



EVN
620 014
4037293620147 EAN/GTIN

415,51 CNY excl. VAT**
plus shipping



15-16 days* (CHN)

Recessed luminaire round 12V GX5.3 50W 620 014, Suitable for surface mounting=no, Suitable for recessed mounting=yes, Suitable for wall mounting=no, Suitable for pendant suspension=no, Suitable for ceiling mounting=yes, Suitable for truss mounting=no, Suitable for pedestal /floor mounting=no, suitable for busbar mounting=no, suitable for clamp mounting=no, suitable for cable system=no, adjustability=rotatable and pivotable, with motion detector=no, with light sensor=no, with light source=no, suitable for number of light sources=1, Socket=GX5.3, housing material=aluminium, surface=untreated, housing color=aluminium, cover material=none, surface brushed=no, type of voltage=AC/DC, nominal voltage=12 V, with control gear=no, dimming dependent on Control gear=no, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX=no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwitch = no, manufacturer-specific dimming h=no, dimming mains voltage modulation=no, dimming trailing edge=no, dimming leading edge=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Reduction=no, dimming Touch and Dim=no, dimming Zigbee=no, dimming with Push button=no, without dimming function=no, reflector=without, light emission=direct, type of protection (IP)=IP20, protection class=III, suitable for lamp power=0.1..50 W, height/depth=35 mm, outer diameter =102 mm, installation height/depth=60 mm, installation diameter=85 mm, number of poles=2, connection type=other, lamp with limited surface temperature "D mark"=no, suitable for computer workstations according to EN 12464-1=no, cover of the Luminaire with thermal insulation material possible = no, rotating and swiveling recessed ceiling light for a variety of indoor applications. Effect lighting, room lighting, accent lighting and much more can be implemented with this light. Thanks to the low-voltage socket, various light sources can be used in the light for a wide range of lighting requirements, regardless of whether it is halogen or LED, which means that there are almost no limits to the design options. Several lights can be operated via one control gear, which means that different light groups can be switched within a room. The swivel angle of the lamp is 45°, the range of rotation is 355°."

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

