

**Reflex sensor - Light scanner with background masking  
FHDK 07P6901/KS35A**



**Baumer**  
FHDK 07P6901/KS35A  
10149512

**1571,03 CNY** excl. VAT\*\*  
plus shipping



15-16 days\* (CHN)

Reflex sensor FHDK 07P6901/KS35A, setting range=2..60 mm, scanning range=10..60 mm, triangulation=background suppression, pre-failure notification=yes, with time function=no, rated switching distance=60 mm, max. switching distance=60 mm, max. output current =100 mA, reflector included in delivery=no, analog output 0 V ... 10 V=no, analog output 0 mA ... 20 mA=no, analog output 4 mA ... 20 mA=no, analog output -10 V ... +10 V=no, with other analog output=no, setting method=teach-in, with analog communication interface=no, with AS-Interface communication interface=no, with CANOpen communication interface=no, with DeviceNet communication interface=no, with Ethernet communication interface=no, With communication interface INTERBUS=no, With communication interface PROFIBUS=no, With communication interface RS-232=no, With communication interface RS-422=no, With communication interface RS-485=no, With communication interface SSD=no, Mi t Communication interface SSI=no, number of semiconductor outputs with signaling function=2, design of the electrical connection=cable with plug connector, design of the switching output=NPN, design of the switching function=closer (NO), explosion protection category for gas=none, explosion protection Category for dust=none, housing design=rectangular, sensor width=8 mm, sensor height=16.2 mm, sensor length=10.8 mm, tactile function=light/dark switching, material of the optical surface=plastic, material of housing=plastic, min. reflector distance=2 mm, ambient temperature=-20..50 °C, response time=0.5 ms, rated control supply voltage Us at DC=10..30 V, type of voltage=DC, with monitoring function of downstream devices=no, laser protection class=none, wavelength of the sensor=660 nm, type of light=red light unpolarized, with restart lock=no, suitable for safety functions=no, degree of protection (IP)=IP65

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

