

## Item Number EB10728807

https://www.eibabo.cn/eaton/main-switch-intermediate-structure-sw-1s-1oe-safety-switch-3-p-15kw-p1-32-y-syb-sw-hi11-eb10728807



# Main switch intermediate structure/sw,1S,1Ö - Safety switch 3-p 15kW P1-32/V/SVB-SW/HI11

### ×

#### **Eaton**

P1-32/V/SVB-SW/HI11 017518 4015080175186 EAN/GTIN

## **531,01 CNY** excl. VAT\*\*

plus **shipping** 



15-16 days\* (CHN)

Main switch intermediate construction/sw,1S,1Ö P1-32/V/SVB-SW/HI11 design as main switch, design as maintenance/repair switch, number of switches 1, max. rated operating voltage Ue at AC 690V, rated operating voltage 690 ... 690V, Rated uninterrupted current lu 32A, rated uninterrupted current at AC-23, 400 V 32A, rated operational power at AC-3, 400 V 13kW, rated short-time withstand current lcw 0.64kA, rated operational power at AC-23, 400 V 15kW, Switching capacity at 400 V 15kW, rated conditional short-circuit current lq 80kA, number of poles 3, number of auxiliary contacts as NC contact 1, number of auxiliary contacts as NO contact 1, number of auxiliary contacts as NO contact 1, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation technology, color of the actuating element black, design of the actuating element door-coupling rotary drive, lockable , connection type main circuit screw connection, degree of protection (IP), on the front IP65, degree of protection (NEMA) 12, main switch, range: main Switch, maintenance switch, repair switch, type identifier: P1, STOP function: HOLD function, with black rotary handle and locking collar, information on scope of delivery: Auxiliary switch contact or neutral conductor can be retrofitted., 3-pole, lockable in 0 position, degree of protection: front IP65, design: intermediate construction, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 15 kW, rated uninterrupted current at AC-23, 400 V and the current at AC-23, 400 V: P = 15 kW, rated uninterrupted current at AC-23, 400 V and the current lcw 0.64kA, rated uninterrupted current lcw 0.64kA, rated uninterrup

#### YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



**DATA PROTECTION** *Guarantee* 

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

