



## Multi-sensor relay - Weather sensors MSR12-UC



**Eltako**

MSR12-UC

22500501

4010312205327 EAN/GTIN

**439,33 CNY** excl. VAT\*\*

plus shipping



4-5 days\* (CHN)

Multi-sensor relay MSR12-UC Type of mounting DIN rail, weather sensor function, presence simulation, run-on function, number of channels 3, time range 5 ... 15min, wind sensor 16 ... 4m/s, rain sensor, temperature sensor 0°C, brightness sensor 1000 ... 60000lx, twilight sensor 1000 ... 60000lx, number of channels 5, control voltage 1 24 ... 24V, type of control voltage 1 DC, rated current 0.05A, rated voltage 24 ... 24V, degree of protection (IP) IP20, width in modular units 2, Width 36mm, height 62mm, depth 58mm, multifunction sensor relay UC for brightness, twilight, wind, rain and frost. Standby loss without multisensor MS only 0.5 watts. The multifunction sensor relay MSR12-UC evaluates the signals of the multisensor MS once every second and, depending on the setting of the rotary switch on the front, issues appropriate control commands to the downstream actuators. The OptoMOS semiconductor outputs switch the voltage present at the universal voltage input terminal +B1. Only 1 multisensor MS can be connected to a multifunction sensor relay MSR12-UC. However, several MSR12-UC can be connected to a multisensor MS, for example to be able to evaluate up to three points of the compass with the light sensors of the MS. The external terminating resistor must only be present with an MSR12-UC. However, it must be removed for further MSR12-UC. At the same time, the power pack supplies the multisensor MS connected to the terminals MS1, MS2, MSA and MSB, including the heating of the rain sensor surface. After the installation, wait about 1 minute for the automatic synchronization. During this time, 3 LEDs light up in regular succession.

## YOUR ADVANTAGES



### WORLDWIDE TRADE

Corporate video eibmarkt®



### COMPLAINTS HANDLING

Obliging and 100% safely



### SHORT DELIVERY TIME

Warehousing



### 99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



### 25 YEARS OF EXPERIENCE

In worldwide mail order



### REFUND

Within 14 days



### DHL TRACK & TRACE

Shipment tracking



### ORDER LIVE CHAT

With order history



### DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

