

Item Number EB10627390

https://www.eibabo.cn/siemens/residual-current-circuit-breaker-with-line-protection-c-16a-1-n-30ma-5s u1356-7kk16-eb10627390



Residual current circuit breaker with line protection C,16A,1+N,30mA 5SU1356-7KK16

×

Siemens

5SU1356-7KK16 4001869306827 EAN/GTIN

264,62 CNY excl. VAT**

plus **shipping**



4-5 days* (CHN)

RCBO type A, 30mA, C16 5SU1356-7KK16 number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated insulation voltage Ui 264V, rated impulse withstand voltage Uimp 4kV, rated current 16A, rated residual current 0.03A, residual current type A, Energy limitation class 3, rated breaking capacity according to EN 61009 6kA, rated breaking capacity according to IEC 60947-2 15kA, rated short-circuit breaking capacity lcn according to EN 61009-1 6kA, instantaneous disconnection characteristic, surge current strength 1kA, type of voltage AC, frequency 50 Hz, tripping characteristic C, switching neutral conductor, with locking device, overvoltage category 3, Pollution degree 2, Ambient temperature during operation -25 ... 55°C, Width in pitch units 2, Installation depth 70mm, Suitable for flush-mounted installation, False tripping protection, Degree of protection (IP) IP20, Connectable conductor cross-section solid 0.75 ... 35mm², Connectable conductor cross-section stranded 0.75 ... 35mm², FI/LS-Sc holder, 6 kA, 1P+N, type A, 30 mA, C-Char, In: 16 A, Un AC: 230 V FI/LS for combined short-circuit protection and protection against accidental contact. The patented RCBOs from Siemens - as an important component of the SENTRON protective devices for electrical installations, enable combined personal fire and line protection in just one device. In addition to detecting fault currents, they also offer reliable protection against short circuits and overload thanks to the integrated overcurrent protection device. The Siemens RCBOs as a combination of residual current circuit breakers and miniature circuit breakers are characterized above all by: 1. Increased operational reliability and system availability thanks to the separate shutdown of the circuit concerned. 2. Whether sinusoidal AC residual currents or smooth DC residual currents - Siemens offers the right type and special designs for all requirements. 3. Reliable safety during installation thanks to the grip and touch protection included as standard. 4. Too

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

