



## Residual current circuit breaker 40/0.5A 4p. F204A-40/0,5



**ABB**

F204A-40/0,5

2CSF204101R4400

8012542784104 EAN/GTIN

**513,61 CNY** excl. VAT\*\*

plus shipping



4-5 days\* (CHN)

FI circuit breaker 40/0.5A 4p. F204A-40/0.5 number of poles 4, rated voltage 400V, rated current 40A, rated residual current 0.5mA, rated insulation voltage  $U_i$  500V, rated impulse withstand voltage  $U_{imp}$  4kV, mounting type DIN rail, residual current type A, short-circuit strength ( $I_{cw}$ ) 1kA, impulse current strength 0.3kA, Frequency 50/60 Hz, additional equipment possible, with locking device, degree of protection (IP) IP2X, width in modular spaces 4, installation depth 69mm, ambient temperature during operation -25 ... 55°C, degree of pollution 2, connectable conductor cross-section stranded 0 ... 25mm<sup>2</sup>, Connectable conductor cross-section solid 25 ... 25mm<sup>2</sup>, Residual current protective devices (RCCBs) offer personal and property protection as well as protection against electrically ignited fires in accordance with DIN VDE 0100-410 and DIN VDE 0100-530. The residual current circuit breakers of the F200 series ensure protection against sinusoidal alternating currents and pulsating currents with a smooth DC residual current component of up to 6 mA to earth. As well as fault protection (protection against indirect contact), additional protection (with  $I_{\Delta n} = 30$  mA) and fire protection (with  $I_{\Delta n} = 300$  mA). They meet the product standards IEC/EN 61008-1, 61008-2-1, 61543 (VDE 0664 10, 11, 30) and for F200 A to 100 A UL 1053. Areas of application are household, commercial and industrial applications. The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the F200 fit for worldwide use.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

