


**Miniature circuit breaker 1-p B6A S201-B6**

**ABB**
**S201-B6**
**2CDS251001R0065**
**4016779464901 EAN/GTIN**
**50,73 CNY** excl. VAT\*\*

plus shipping



4-5 days\* (CHN)

Automatic circuit breaker 6kA 6A B 1p S201-B6 tripping characteristic B, number of poles (total) 1, number of fused poles 1, rated current 6A, rated voltage 230V, rated insulation voltage  $U_i$  440V, rated impulse withstand voltage  $U_{imp}$  4kV, rated switching capacity  $I_{cn}$  according to EN 60898 at 230 V 6kA, rated switching capacity  $I_{cu}$  according to EN 60898 at 400 V 6kA, rated switching capacity  $I_{cu}$  according to IEC 60947-2 at 230 V 10kA, rated switching capacity  $I_{cu}$  according to IEC 60947-2 at 400 V 10kA, type of voltage AC/DC, frequency 50 ... 60Hz, energy limitation class 3, overvoltage category 3, degree of pollution 2, additional equipment possible, width in module widths 1, installation depth 69mm, degree of protection (IP) IP20, ambient temperature during operation -25 ... 55°C, connectable conductor cross-section stranded 0 ... 25mm<sup>2</sup>, connectable conductor cross-section solid 0 ... 35mm<sup>2</sup>, The S 200 series circuit breakers protect cables and lines from overload and short circuits in accordance with DIN VDE 0100-430 and DIN VDE 0100-530. They meet the building regulations DIN VDE 0641-11 or IEC/EN 60898-1, DIN VDE 0660-101 or IEC/EN 60947-2 and UL1077. Its patented connection terminal ensures simple and safe contacting and handling by means of a pressure plate. For better visibility when wiring, the connection opening for cables is above the connection opening for the busbar. Conductor cross-sections up to 35 mm<sup>2</sup> can be connected directly to the device via the connection terminal with insulation in protection class IP20. The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the S 200 fit for worldwide use. Before delivery, each device is subjected to three intensive tests for quality and performance.

**YOUR ADVANTAGES**

**WORLDWIDE TRADE**
*Corporate video eibmarkt®*

**99% CUSTOMER SATISFACTION**
*> 500,000 customers worldwide*

**DHL TRACK & TRACE**
*Shipment tracking*

**COMPLAINTS HANDLING**
*Obliging and 100% safely*

**25 YEARS OF EXPERIENCE**
*In worldwide mail order*

**ORDER LIVE CHAT**
*With order history*

**SHORT DELIVERY TIME**
*Warehousing*

**REFUND**
*Within 14 days*

**DATA PROTECTION**
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). **eibabo®** is a company of eibmarkt.com GmbH. **eibmarkt.com GmbH** is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

