

Item Number EB10708728

https://www.eibabo.cn/siemens/motor-protection-circuit-breaker-2a-3rv1011-1ba10-eb10708728



Motor protection circuit-breaker 2A 3RV1011-1BA10

×

Siemens

3RV1011-1BA10 4011209263536 EAN/GTIN

439,33 CNY excl. VAT**

plus **shipping**



4-5 days* (CHN)

Circuit breaker 1.4-2A N24A 3RV1011-1BA10 overload release current setting 1.4 ... 2A, setting range of the instantaneous short-circuit release 26 ... 26A, with thermal protection, sensitive to phase failure, magnetic tripping technology, rated operating voltage 690 ... 690V, rated uninterrupted current lu 2A, Rated operational power at AC-3, 230 V 0.37 kW, rated operational power at AC-3, 400 V 0.75 kW, connection type main circuit screw connection, design of the actuating element rocker arm, device design built-in device fixed installation technology, number of poles 3, rated limiting short-circuit breaking current lcu at 400 V, AC 100kA, protection class (IP) IP20, height 90mm, width 45mm, depth 75mm, size S00 circuit breaker for motor protection, CLASS 10 A release 1.4...2 A N release 26 A screw connection Standard switching capacity SIRIUS 3RV1 circuit breaker for motor protection for safe disconnection at Short-circuit and protection of consumers and system against overload, as well as for safe disconnection of the system from the network. The compact and climate-proof circuit breakers are optimized for use in consumer feeders due to their low heat dissipation, of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (eg IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection, as main and EMERGENCY STOP switches and for use in IT networks. They are available with a screw connection and optionally with a built-in auxiliary switch. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV29 infeed system, significantly reduces the main circuit wiring. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADECorporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

