

Item Number EB10708729

https://www.eibabo.cn/siemens/motor-protection-circuit-breaker-2-5a-3rv1011-1ca10-eb10708729



Motor protection circuit-breaker 2,5A 3RV1011-1CA10

×

Siemens

3RV1011-1CA10 4011209263543 EAN/GTIN

437,38 CNY excl. VAT**

plus shipping



4-5 days* (CHN)

Circuit breaker 1.8-2.5A, N30A 3RV1011-1CA10 overload release current setting 1.8 ... 2.5A, setting range of the instantaneous short-circuit release 33 ... 33A, with thermal protection, sensitive to phase failure, magnetic tripping technology, rated operating voltage 690 ... 690V, rated uninterrupted current lu 2.5A, rated operational power at AC-3, 230 V 0.37kW, rated operational power at AC-3, 400 V 0.75kW, connection type main circuit screw connection, design of the actuating element rocker arm, device type built-in device fixed installation technology, number of poles 3, rated limiting short-circuit breaking current lcu at 400 V, AC 100kA, degree of protection (IP) IP20, height 90mm, width 45mm, depth 75mm, circuit breaker size S00 for motor protection, CLASS 10 A release 1.8...2.5 A N release 33 A screw connection, standard switching capacity Circuit breaker SIRIUS 3RV1 for motor protection for safe shutdown in the event of a short circuit and protection of consumers and system against overload, as well as for safe separation of the system from the mains. The compact and climate-proof circuit-breakers are optimized for use in consumer feeders due to their low waste heat, of course also for IE3/IE4 motors and equally for switching direct current. Worldwide approvals (eg IEC and UL/CSA) and use in potentially explosive applications (ATEX or IEC Ex) are a matter of course. Device variants are available for motor protection, as main and EMERGENCY STOP switches and for use in IT networks. They are available with a screw connection and optionally with a built-in auxiliary switch. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc., is the same for all sizes. The use of various power supply options, such as the associated SIRIUS 3RV29 infeed system, significantly reduces the main circuit wiring. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADECorporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

