

IP65

FITIN

https://www.eibabo.cn/eaton/main-switch-i-g-svb-safety-switch-3-p-5-5kw-t0-2-1-i1-svb-eb10712075

## Main switch I (G)/SVB - Safety switch 3-p 5,5kW T0-2-1/I1/SVB

Eaton T0-2-1/I1/SVB 207147 4015082071479 EAN/GTIN

## 256,16 CNY excl. VAT\*\*

plus shipping



Main switch I(G)/SVB T0-2-1/I1/SVB Design as a main switch Design as a maintenance/repair switch Design as a safety switch Design as an EMERGENCY STOP device Number of switches 1 Max. rated operating voltage Ue at AC 690V, rated operating voltage 690 ... 690V, rated continuous current Iu 20A, rated continuous current at AC-23, 400 V 13.3A, rated continuous current at AC-21, 400 V 20A, rated operational power at AC-3, 400 V 5.5kW, rated short-time withstand current Icw 0, 32kA, rated operational power at AC-23, 400 V 5.5kW, switching capacity at 400 V 5.5kW, conditional rated short-circuit current Iq 6kA, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 0, device design complete device in the housing, suitable for floor mounting, color of the actuating element red, design of the actuating element door-coupling rotary drive, lockable, connection type main circuit screw connection, protection delicate (IP), front IP65, degree of protection (NEMA) other, main switch, range: main switch, maintenance switch, repair switch, type identifier: T0, STOP function: EMERGENCY STOP function, with red rotary handle and yellow locking ring, 3-pole, lockable : lockable in 0 position, degree of protection: IP65, design: surface mounting, switching angle: 90 °, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, rated continuous current: Iu = 20 A, 2 unit(s), Standards and regulations: IEC/EN 60947, VDE 0660, IEC/EN 60204, load-break switch according to IEC/EN 60947-3

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



×