Item Number
EB10712273

28.03.2024/13:48

https://www.eibabo.cn/eaton/power-contactor-1no-4kw-400v-ac-dilm9-10-230v50-60hz-magnet-contactor-9a-230vac-0vdc-dilm9-10...-eb10712273



Power contactor 1NO 4kW/400V,AC DILM9-10 (230V50/60HZ - Magnet contactor 9A 230VAC 0VDC DILM9-10(...

Eaton
DILM9-10(230V50/60HZ)
276698
4015082766986 EAN/GTIN

244,58 CNY excl. VAT**
plus **shipping**

4-5 days* (CHN)

Power contactor 1NO 4kW/400V,AC DILM9-10(230V50/60HZ Rated control supply voltage Us at AC 50 Hz 230 ... 230V, rated control supply voltage Us at AC 60 Hz 230 ... 230V, rated control supply voltage Us at DC 0V, type of voltage for actuation AC, rated operational current Ie at AC-1, 400 V 22A, rated operational current Ie at AC-3, 400 V 9A, rated operational power at AC-3, 400 V 4kW, rated operational current Ie at AC-4, 400 V 6A, rated operational power at AC-4, 400 V 2.5kW, rated operational power NEMA 3.7kW, number of auxiliary contacts as NO contact 1, number of auxiliary contacts as NC contact 0, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, application: power contactor for motors, Power contactors up to 170 A, 3-pole, Utilization category: AC-1: non-inductive or weakly inductive load, resistance furnaces, AC-3: squirrel-cage motors: starting, switching off during operation, AC-4: int Ignition motors: starting, counter-current braking, reversing, jogging, Connection technology: screw terminals, Note: Also suitable for motors of efficiency class IE3., IE3-capable devices are marked with the logo on the packaging., Poles: 3-pin, rated operational current AC-3 380 V 400 V: Ie= 9 A, rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = Ie= 22 A, encapsulated: Ith= 18 A, rated operational current AC-1 conventional thermal current 1-pole open: Ith= 50 A, encapsulated: Ith= 45 A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: P= 2.5 kW, 380 V 400 V: P= 4 kW, 660 V 690 V: P= 4.5 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 1.5 kW, 380 V 400 V: P= 2.5 kW, 660 V 690 V: P= 3.6 kW , Can be combined with auxiliary switches: DILM32-XHI.., DILA-XHI(V).., Contact equipment S = NO contact: 1 NO, Notes: Contact elements according to EN 50012., Type of current AC/DC: Alternating current operation

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

COMPLAINTS HANDLING
Obliging and 100% safely

SHORT DELIVERY TIME
Warehousing

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

25 YEARS OF EXPERIENCE
In worldwide mail order

REFUND
Within 14 days

DHL TRACK & TRACE
Shipment tracking

ORDER LIVE CHAT
With order history

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online