



## Main switch emergency stop/intermediate structure - Safety switch 3-p 55kW P3-100/V/SVB



**Eaton**  
P3-100/V/SVB  
088558  
4015080885580 EAN/GTIN

**1059,73 CNY** excl. VAT\*\*  
plus shipping

 15-16 days\* (CHN)

Emergency stop main switch/intermediate structure P3-100/V/SVB Version as main switch, Version as maintenance/repair switch, Version as EMERGENCY STOP device, Number of switches 1, Max. rated operating voltage  $U_e$  at AC 690V, rated operating voltage 690 ... 690V, rated uninterrupted current  $I_u$  100A, rated uninterrupted current at AC-23, 400 V 100A, rated uninterrupted current at AC-21, 400 V 100A, rated operational power at AC-3, 400 V 37kW, rated short-time withstand current  $I_{cw}$  2kA, rated operational power at AC-23, 400 V 55kW, Switching capacity at 400 V 55kW, rated conditional short-circuit current  $I_k$  4kA, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation technology, color of the actuating element red, design of the actuating element door-coupling rotary drive, lockable, connection type main circuit screw connection, degree of protection (IP), on the front IP65, degree of protection (NEMA) 12, main sc holder, range: main switch, maintenance switch, repair switch, type code: P3, STOP function: EMERGENCY STOP function, with red rotary handle and yellow locking collar, information on scope of delivery: auxiliary switch contact or neutral conductor can be retrofitted., 3-pole, lockability: lockable in 0 position, degree of protection: front IP65, design: sandwich, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 55 kW, rated continuous current:  $I_u$  = 100 A, standards and regulations: IEC/EN 60947, VDE 0660, IEC/ EN 60204, CSA, UL, load-break switch according to IEC/EN 60947-3, NEMA12

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

