2-fold pushbutton with LED, 2 NO contacts, 2 NC contacts M22-I3-M2

Eaton
M22-I3-M2
216533
4015082165338 EAN/GTIN

483,49 CNY excl. VAT**
plus **shipping**

4-5 days* (CHN)

2F pushbutton 2S2Ö, surface-mounted, with LED M22-I3-M2 Number of command points 3, number of pushbuttons 2, number of indicator lights 1, number of key switches 0, number of selector switches 0, number of mushroom buttons 0, rated control supply voltage Us at AC 50 Hz 85 ... 264V, rated control supply voltage Us at AC 60 Hz 85 ... 264V, rated control supply voltage Us at DC 0V, color of the upper part of the housing grey, material of the housing plastic, number of contacts as NO contact 2, number of contacts as NC contact 2, number of contacts as changeover contact 0, degree of protection (IP) IP67/IP69K, degree of protection (NEMA) 4X, housing, range: RMQ-Titan, complete device, design: housing, momentary, connection type: screw connection, description: indicator light white, LED element, 85 - 264 V AC, command points: 2 number, color of housing cover: grey, color RAL value: RAL 7035, degree of protection: IP66, IP67, IP69K, connection to SmartWire-DT: no, contacts NC = NC: 2 NC, contacts S = Normally open: 2 NO, contact assembly note eis = safety function, through positive opening according to IEC/EN 60947-5-1, travel of the control panel and actuating force according to DIN EN 60947-5-1, K.5.4.1 positive opening travel: mm 4.8, maximum travel: mm 5.7, minimum force for positive opening: N 15, front dimensions: 153 x 80, standards and regulations: IEC/EN 60947, VDE 0660, installation position: any

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee